Assembly Instructions - Model Chu-ko-nu



D) Not shown. Wind rubber bands tightly around entire assembly to clamp while the glue dries. The rubber bands should force the top and bottom to bend to the same curvature as the stock.

Step 2: Handles and Cheeks

- A) Glue the toothpick into the two small holes on the stock cheeks. Just make the toothpick snug.
 - B) Glue the three parts of the lever handle together, taking care to line them up.
 - C) Glue the four parts of the stock handle together as shown, taking care to line them up.



Secure the handles together with rubber bands if desired, and set aside to dry.

Step 3: The Bolt Box (or Magazine)

A) Lay the two bolt box sides with their best sides downward in mirror position. Apply a thin bead of glue to the lines shown in green. Do not use too much glue.

Bottom

B) Place the front, back, bottom, and top parts into their sockets, taking care to engage the tab on the front and top. Turn the other side over, and glue it down in place.





Тор

C) Secure the two sides on the bolt box with rubber bands while the glue dries.



These instructions are best used along with the video instructions posted on our site: www.MorrisModels.com. Model outlines and text Copright (C) Don Morris, 2020.



B) After glue dries, set the magazine in place over the cheek, with the pointed toothpick end in the slot as shown.



C) Add glue as shown in green, then glue down the other stock cheek, pointy end in the bolt box slot. Let dry.

Step 7 Alternative: Use the bow to help with alignment, and glue both cheeks onto assembly at the same time, over the bolt box. This is the method shown in the video. In any case, the box should now be attached, but moveable.

Step 8: The Lever

Ease the lever into the position shown, and pin the two holes with the 1/4" (6 mm) pins. Secure with dabs of glue on the outside layers only.







Hold the front and rear bows together, as shown. Gently slide them into the socked in the stock. Be careful, as they may fit quite tightly. Also note that they may have small splinters on them, so a light sanding before assembly is a good idea.

Step 10: The Bowstring

Tie small loops in the ends of the bowstrings. The bowstring should be 11" (28 cm) long end to long end. Insert the string through the large hole at the back of the slots. Carefully bend the bow, and slip the loops over the nubs at the ends of the bow. (Not Shown.)

Operating: Put pea-sized lumps of modelling clay in the ends of the coffee stirrers. Drop them into the bolt box, clay side forward. Pump the lever forward until the bowstring clicks into place. Pull backwards to fire. Warning: As with any toy that fires, this toy presents an eye hazard. Wear eye protection while firing this model. Additionally, ensure that any other people in the area are also wearing eye protection. This model is intended for use only by or under the supervision of competent adults.